



◆ SPECIFICATION

Model NO.	LBE904XSL200	LBE904XS400
Camera		
Image Sensor	IMX290	OV4689
Main processor	HI3516D	HI3516D
Resolution	1080P	4MP
Effective Pixels	1945(H)*1097(V)	2688(H)*1520(V)
Compression	H.264/H.265/JPEG/AVI/MJPEG	H.264/H.265/JPEG/AVI/MJPEG
TV System	PAL/NTSC	
Electronic Shutter Time	Auto: PAL 1/1-1/10000Sec; NTSC 1/1-1/10000Sec	
S/N Ratio	≥52dB	
Scanning System	Progressive	
Video Output	Network	
Lens		
Focus Length	2.8-8mm	2.8-8mm
Focus Control	Auto	Auto
Lens Type	Motor Zoom Auto Focus	Motor Zoom Auto Focus
Pixels	3M Pixels	5M Pixels
Night Vision		
Infrared LED	42μ x 6PCS	
Infrared Distance	90M	
IR Status	Under 10 Lux By CDS	
IR Power On	CDS Auto Control	
Network		
Ethernet	RJ-45 (10/100Base-T)	
Protocol	TCP/IP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, NTP, SMTP	
ONVIF	Support ONVIF 2.4	
P2P	YES, Support QR Code	
POE	Optional, Support IEEE 802.3af	
WIFI	N/A	
Video Delay	0.3S (Within the Lan)	
Main Stream 1	1920*1080@30fps	2560*1440@20fps
Main Stream 2	/	2304*1296@30fps
Main Stream 3	/	1920*1080@30fps
Sub Stream 1	720*480@30fps	720*480@20fps 720*480@30fps
Sub Stream 2	/	/
Sub Stream 3	/	/
Tri Stream	352*288@30fps	352*288@20fps 352*288@30fps
IE Brower	IE8-11, Google Chrome, Firefox, Safari, Mac Safari	
Smart Phone	iPhone, iPad, Android, Android Pad	
Camera Features		
Day/Night	Color/ B&W (IR-CUT)	
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR , White Balance, BLC, FLK(Flicker Control)	
Corridor Pattern	Support	Support
Defog Mode	Support	Support
ROI	Support	Support
BLC	Support	Support
HDR	/	/
WDR	Support	Support
Motion Detection	Support	Support
Privacy Masking	3 Rectangular Zone	
Recording Mode	NVR/NAS/CMS/Web	
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Farsi, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Netherlands	
General		
Housing	Plastic, IP66	
Anti-cut Bracket	YES, Anti-Cut Bracket	
IR Cut Filter	YES	
Operation Temperature	-20℃ ~ +60℃ RH95% Max	
Storage Temperature	-20℃ ~ +60℃ RH95% Max	
Power Source	DC12V±10%, 1000mA	
Dimension	290(W) x 177(H) x 107(D)mm	
Weight	1.9Kg	