



Volcano Tag™



DURABLE LOW FREQUENCY RFID TAGS THAT PERFORM IN HIGH TEMPERATURE ENVIRONMENTS

- **High heat tolerance** – during storage, industrial processing, transportation and outdoor use
- **Durable housing** – withstands rigors of chemical and mechanical exposure
- **Versatile** – screw-mounts securely anywhere without compromising performance: glass, metal, plastic, or wood

Volcano Tag™ passive contactless radio frequency identification (RFID) transponders are built for reliable performance in high-heat conditions. For RFID applications where tags must perform before, amidst or following extreme heat exposure, Volcano Tag discs withstand peak temperatures up to 392° F (200° C).

Volcano Tag housings are composed of field-proven, temperature-stable polyphthalamide (PPA). This thermoplastic shell holds its shape despite high or fluctuating temperatures, protecting the electronics within. Exceptional toughness, chemical resistance and abrasion resistance assure consistent communications with RFID readers, and reliable performance in automation and manufacturing applications.

Low frequency (LF) Volcano Tag discs perform well affixed to virtually any surface – glass, metal, plastic or wood. They offer reliable, cost-effective tagging for near-proximity reader applications, with available data storage from a 64-bit user ID up to 264-bit read-write capability.

For additional disc-tag options, the HID Global IN Tag™ and Poly Tag families also include heavy-duty tags in low frequency, high frequency and UHF configurations. For lighter-duty applications, consider HID Epoxy Disc or World Tag™ RFID tags.

TECHNOLOGY HIGHLIGHTS:

- Peak temperature up to 392° F (200° C)
- Operating frequency 125 kHz
- Up to 264 EEPROM
- Waterproof
- Mount-ready, via central screw hole

APPLICATION AREAS:

- Automation and manufacturing
 - High temperature production processes
 - Machinery

SPECIFICATIONS


HID Global can create a custom tag solution to fit your application requirements for chip type, dimensions, programming and materials.

Volcano Tag™	
231	
Base Model Number	612170 601170
ELECTRONIC	
Operating Frequency	125 kHz
Chip Type	Q5 Unique
Memory	264 bit EEPROM 64 bit read-only
Anti-Collision	
Reading Distance	Dependent upon reader, environment and application
PHYSICAL	
Dimensions	Ø 1.02 x 0.16 in (Ø 26 x 4 mm)
Mounting Method	Screw
Fixation Hole Size	Ø 0.18 in (4.5 mm)
Affixes To	Glass, metal, plastic, wood
Housing Material	PPA
Color	Black
Weight	0.12 oz (3.5 g)
CHEMICAL AND MECHANICAL	
Water	IP68, 68° F (20° C), 3.3 ft (1 m) x 24 h
Vibration	IEC 68.2.6 [10 g, 10 to 2000 Hz, 3 axis, 2.5 h]
Shock	IEC 68.2.29 [40 g, 18 ms, 6 axis, 2000 times]
THERMAL	
Storage	-13° to +284° F (-25° to +140° C), 1000 h
Operating	-13° to +185° F (-25° to +85° C)
Shock/Fatigue	68° to +320° F (20° to +160° C), 100 x 5 min with 20 sec transition
Peak	+320° F (+160° C) 1 x 100 h; 392° F (+200° C) 10 x 10 min
OTHER	
Box Size	800 pcs
Warranty	2 Years



hidglobal.com

North America: +1 512 776 9000
 Toll Free: 1 800 237 7769
 Europe, Middle East, Africa: +44 1440 714 850
 Asia Pacific: +852 3160 9800
 Latin America: +52 55 5081 1650

© 2014 HID Global Corporation/ASSA ABLOY AB. All rights reserved. HID, HID Global, the HID Blue Brick logo, the Chain Design, IN Tag, World Tag and Volcano Tag are trademarks or registered trademarks of HID Global or its licensor(s)/supplier(s) in the US and other countries and may not be used without permission. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners.

2014-08-18-hid-rfid-il-volcano-tag-ds-en PLT-00285

An ASSA ABLOY Group brand

ASSA ABLOY